



31 Hedley Road
St Albans
Hertfordshire
AL1 5JL

t: +44 (0) 1727 830151
f: +44 (0) 1727 855993
e: info@camstage.com
w: www.camstage.com

Matt Plus

Matt plus screens are considered by leading cinema exhibitors and laboratories worldwide to be the 'premier' non-coated projection surface. The flexible PVC based material and coating is manufactured to a unique formulation and specification, providing wide viewing angle. High contrast, bright pictures and excellent colour temperature. Noted for invisible seams under normal projection conditions.

	Matt Plus	Matt Plus MP	Matt Plus MPS
Application	Cinemas, Home Theatre, Roller Screen	Preview Theatre, Cinema, Screening Room, Home Theatre, Roller Screen	
View Distance	Minimum of 5 mtr (15') recommended on perforated surfaces	Minimum of 1.5m (5')	
Maximum Size	No maximum size limit.	5.2m x 2.2m (17' x 7.2')	
Perforation Size	1.2mm (0.047")	0.50mm (0.020")	
Perforation Density	4.5%	1.7%	5.1%
Weight	0.43kg/m ² (0.10ib/ft ²)	0.50kg/m ² (0.10ib/ft ²)	
Eyelet Spacing	150mm (6") nominal (US) / 200mm(8") France	150mm (6") nominal	
Typical packing	Folded in parcel box up to 90m ² (1000ft ²). Wooden crate for larger sizes. Can also be tube packed long box 7m (23')	Rolled in cardboard tube	
Fire Certificate	UK BS 5867 Part2, USA NFPA 701, Canada CAN ULC S102-2, France M1, Germany B1, Spain M2, Italy Class1, Japan BT-08-050 (regulation requires certification from importing country) and Australia		
Surface Edge Options	<ul style="list-style-type: none"> • Web and eye (grommet). Triple fold web integral with surface. • Performed pipe pocket any size on any side. • Cloth web fixings (snaps) for press stud frames. • Straight sides or shaped to special order. • Cut square (unfinished edge) 		

Despatch/ Storage

Screens should normally be transported and stored at temperatures between 5c and 30 c (40F and 85F), with relative humidity less than 80%. If screens are very cold (e.g. following air transport) then they must be allowed to warm up before unpacking. Otherwise cold cracking may occur. Screens should be installed within a maximum 2 months of shipping. Packages should be handled with care to avoid damage.

Care /Maintenance

The general environment where the screen is installed should be kept reasonably clean to avoid dirt and dust build up. Screens can be periodically cleaned using a soft brush or cloth, doing this vertically with limited pressure. Screens can be cleaned using a damp wetted cloth with water and mild detergent. Under no circumstances should screens be cleaned with an abrasive material or harsh chemicals such as acid, bleaches or solvents. Manufacturer is not liable for damage caused to screens through the use of inappropriate cleaning methods or chemicals.

Installation

Stage Shop Ltd t/a camstage have a large number of professional Installation engineers available to carry out any type of screen installations, please feel free to contact us at camstage we would be more than happy to arrange a competitive installation price for your consideration.

